

# Aerosol Touch-Up Instructions



## **DIRECTIONS: Single Step Finishes**

1. Surface must be clean and free from grease, rust and wax. Mask off or protect area from overspray.
2. Allow the can to warm to room temperature.
3. SHAKE can until the mixing balls inside break free and rattle. Shake 2 minutes, swirling container so balls travel the bottom grove of the can.
4. Repeat the shaking procedure for at least 10 seconds after each minute or spraying.
5. Test spray on a piece of cardboard for proper distance. If too far away from surface, coverage will be uneven.
6. APPLY with “dusting strokes”. Allow the paint to become tacky before applying next coat.
7. If spray stops, or is irregular, twist the spray head from side to side without removing it.
8. Never spray with valve only partly open. Press the spray head all the way down to can.
9. When finished painting, you will need to clean the valve. Hold can upside down and spray for two seconds.

## **DIRECTIONS: Multi Step Finishes – Review Above Directions First Before Starting**

Test All Steps on a piece of cardboard first to simulate finish.

1. Apply an even layer of “Step #1” base coat first (see Single step finish above).
2. Apply “Step #2” by holding can approximately 15” from area. Apply to area by spraying with “dusting strokes”. Allow the paint to become tacky before applying the next coat.
3. Finishes with a third step, apply “Step #3” using “Step #2” directions.

**WARNING:** Avoid breathing vapors or spray mist. Open windows and doors to ensure fresh air during application and drying. If you experience watering eyes, headaches or dizziness, increase the fresh air, wear a NIOSH approved respirator or leave the area. Avoid contact with skin or eyes.

**DANGER:** Vapor may ignite explosively. Prevent vapor build-up. Keep from sparks, heat, flame or other heat sources. Do not smoke. Turn off pilot lights, stoves, heaters electrical motors and other sources of ignition until all vapors are gone. Do not puncture, incinerate (burn) or place containers in garbage compactor. Prolonged exposure to heat or sun may cause bursting. Do not expose to heat or store over 120°F.

**FIRST AID:** In case of eye contact, flush immediately with water. Seek medical attention. For skin, wash with soap and water. If affected by vapor or mist, remove to fresh air. If swallowed, do not induce vomiting, get medical attention.

For additional instructions and warning information, please review aerosol can.

KEEP OUT OF REACH OF CHILDREN.

Questions or Comments, please contact your local sales representative or customer service at (800) 776-9533.

Rev011910gh

